


Digi Connect™ EM Family

Wired and Wireless Embedded Modules



The Digi Connect EM and the Digi Connect Wi-EM are the industry's first interchangeable embedded modules, delivering wired and wireless Ethernet network connectivity that is cost-effective and easy to implement.



Seamless migration to total integration

Future proof protection - software development migrates fully to chip solutions.

Features/Benefits

- Interchangeable and pin-compatible single-component solution based on 32-bit NET+ARM processor
- 4MB Flash and 8MB RAM on board
- Two high-speed TTL serial interfaces with up to 230 Kbps throughput
- Serial Peripheral Interface (SPI) with up to 9 Mbps throughput
- Wireless Ethernet network interface
 - 802.11b network interface with data rates up to 11 Mbps
 - WPA security and WEP encryption
 - Dual diversity antenna setup
 - FCC module approval improves time-to-market
- Wired Ethernet network interface
 - Auto-sensing 10/100Base-T network interface
- Nine shared GPIO port options
- Low power consumption and industrial temperature range
- Population options for design flexibility
- Strong SSL/TLS encryption for security sensitive environments
- Plug-and-play firmware option eliminates embedded software development effort
- Easy-to-use and royalty-free NET+Works development platform for custom application development

Overview

Wireless technology creates a new dimension in a rapidly emerging world of ubiquitous networking collaboration in which billions of networked electronic devices work invisibly and jointly with each other and with people. Making the right network technology decisions is a key factor for market success and defines the competitive edge of your products.

The Digi Connect™ EM family of embedded modules enables original equipment manufacturers to keep pace with ever-evolving networking technology by delivering complete and versatile embedded network connectivity solutions. They are cost-effective and easy to implement in existing and new product designs, while powerful enough to meet your future product performance needs.

Based on a unique common platform design approach, the Digi Connect EM and Digi Connect Wi-EM embedded modules offer complete “drop-in” integration. This allows you to build future-proof products based on a single design supporting 10/100Base-T wired and 802.11b wireless Ethernet connectivity. Digi Connect EM embedded modules make all of this possible without the traditional complexities of hardware and software integration work, and at a fraction of the time and cost required to create custom solutions.

The Digi Connect EM and Digi Connect Wi-EM embedded modules feature a variety of connectivity options, such as two high-speed serial ports, a nine Mbps SPI master mode interface and nine General Purpose Input/Output (GPIO) port options. For additional integration flexibility, they are available in two low-profile population options, with or without onboard LED array and an Ethernet connector. Additional customer-specific population options are available on request.

Built on leading NetSilicon 32-bit NET+ARM technology, Digi Connect embedded modules combine true plug-and-play functionality with the freedom and flexibility of complete software customization. The proven NetSilicon NET+Works® development platform provides a seamless migration path to a fully integrated NetSilicon system-on-chip solution.

Please contact us at 1-877-OEM-DIGI or 952-912-3444 for additional information or to discuss your specific application requirements.




Connectware™

Plug-and-Play Modules

The Digi Connect EM and Digi Connect Wi-EM embedded modules with plug-and-play firmware deliver instant and completely transparent wired and wireless device server networking functionality. They significantly reduce time to market by completely eliminating the need for additional embedded hardware or software development.


Unique and industry-leading features such as a robust TCP/IP stack, universal IP address assignment, integrated web server with user file system, fully customizable web user interface, custom Java applet support, enhanced security with strong DES/3DES/AES encryption based on the SSL/TLS standard, intelligent device management via SNMP, and patented RealPort® COM/TTY port redirection make it an ideal solution for any application that requires versatility and performance.

The Digi Connect Integration Kit provides a platform for evaluation, rapid prototyping, and integration of Digi Connect embedded modules with plug-and-play firmware. It offers the tools, sample code, and documentation that make easy product integration and web-based product customization possible.




SOFTWARE FEATURES

- Robust on-board TCP/IP stack with built-in web server
 - TCP, UDP, DHCP, SNMP, SSL/TLS, Telnet, Rlogin, RFC 2217, LPD, HTTP/HTTPS, SMTP, ICMP, IGMP, ARP
- Universal IP address assignment
 - Static IP, DHCP, Auto-IP
- Secure web-based configuration (HTTP/HTTPS)
- Fully customizable web interface with support for custom Java applets
 - Applet space: 512 kb
- Telnet Command Line Interface
- Low-level serial configuration interface
- User-defined network service configuration
 - HTTP/HTTPS, Telnet, Rlogin, ADDP, SNMP, RealPort, SSL/TLS, TCP/UDP
- TCP/UDP forwarding characteristics
 - Bytes, Idle Time, Data Pattern
- User-configurable TCP/UDP Socket ID string
- Event notification (SMTP/SNMP traps)
 - GPIO Status, Data Pattern
- Intelligent SNMP device management
 - RFC 1213/1215/1316/1317
- Strong SSL v3.0/TLS v1.0 based encryption
 - DES (56-bit)
 - 3DES (168-bit)
 - AES (128/256-bit)
- Patented RealPort® COM/TTY port redirection for Microsoft Windows, UNIX, and Linux environments



Customizable Modules




Removing the complexities of traditional hardware design efforts, the customizable versions of the Digi Connect EM and Digi Connect Wi-EM embedded modules enable customers to quickly and cost-effectively implement and deploy application-specific and future-proof embedded software solutions for wired and wireless network environments.

Based on the easy-to-use and royalty-free NetSilicon NET+Works development platform, the Digi Connect Development Kit delivers a complete out-of-the-box solution for embedded software development including all the integrated building blocks that are required to quickly and cost-effectively create secure and fully network-enabled product solutions.

The common NetSilicon development platform provides a seamless migration path to a fully integrated NetSilicon system-on-chip solution using the award-winning family of network-enabled NET+ARM processors. It also minimizes design risk and significantly accelerates the overall embedded software development process.

DEVELOPMENT KIT FEATURES

- Digi Connect embedded module w/JTAG
- Development board
- Macraigor Raven JTAG debugger
- Microcross™ GNU X-Tools with command line and visual GDB debugger
- ThreadX Realtime Operating System with picokernel™ architecture
 - Requires less than 25 kb kernel code space
- Fusion™ TCP/IP stack with full networking protocol and extended network services support
 - TCP, UDP, ICMP, IGMP, DNS, SNMPv2, LDAP, POP, SMTP, PPP, FTP, SNMP, Telnet, FastIP, Fast Sockets, Multi-Homing
- Universal IP address assignment through Address Configuration Executive (ACE)
 - Static IP, DHCP, BOOTP, Auto-IP, RARP, ARP-Ping
- Allegro Software Embedded Web Server
- SSL 3.0/TLS 1.0 with strong encryption
 - DES, 3DES, AES
- Flexible and robust file system supporting RAM and Flash (with wear leveling)
- SMICng MIB Compiler
- Micro XML SAX Parser
- Additional utilities
 - HTML-to-C Compiler
 - Flash download
 - Sample code
- Documentation
 - Hardware reference manual
 - Programmer's guide
 - API reference
 - Advanced web server toolkit



Features/Specifications

HARDWARE

- 32-bit NET+ARM high-performance RISC processor (NS7520 @ 55MHz)
- On-board memory 4MB Flash and 8MB RAM
- On-board power supervisor
- Two high-speed TTL serial interfaces
 - Throughput up to 230 Kbps
 - Full signal support for TXD, RXD, RTS, CTS, DTR, DSR and DCD on port 1
 - TXD / RXD signals support on port 2
 - Hardware and software flow control
- Nine shared General Purpose Input/Output (GPIO) ports
- Wave-solderable design (no clean flux process)

NETWORK INTERFACE

Digi Connect EM

- Standard: IEEE 802.3
- Physical Layer: 10/100Base-T
- Data rate: 10/100 Mbps (auto-sensing)
- Mode: Full or half duplex (auto-sensing)
- Connector: RJ-45 or pin header

Digi Connect Wi-EM

- Standard: IEEE 802.11b
- Frequency: 2.4 GHz
- Data rate: Up to 11 Mbps with automatic fallback
- Modulation: CCK (11/5 Mbps), DQPSK (2 Mbps), DBPSK (1 Mbps)
- Transmit power: 15 dBm
- Receive sensitivity: -87 dBm @ 11 Mbps
- Antenna connector: 2 x RP-SMA
- Security: WPA, WEP encryption (64-/128-bit)

MODEL PART NUMBERS

Model	North America	International
Custom Application		
Digi Connect EM Development Kit	DC-EM-02T-GN	DC-EM-02T-GN
Digi Connect Wi-EM Development Kit	DC-WEM-02T-GN	DC-WEM-02T-GN
Plug-and-Play Firmware		
Digi Connect EM Integration Kit	DC-EM-02T-KT	DC-EM-02T-KT
Digi Connect Wi-EM Integration Kit	DC-WEM-02T-KT	DC-WEM-02T-KT

Bulk packs and customer-specific packaging for individual units available. Population options available.

ENVIRONMENTAL

- Ambient operating temperature: -40° C to 85° C (-40° F to 185° F)
- Relative humidity: 5% to 95% (non-condensing)
- Altitude: 12,000 ft (3685 m)

REGULATORY APPROVALS (IN PROGRESS)

- FCC, Part 15 Class B
- EN 55022, Class B
- EN 61000-3-2 and EN 61000-3-3
- ICES-003, Class B
- VCCI, Class II
- AS 3548
- FCC Part 15 Subpart C Section 15.247
- IC (Industry Canada) RSS-210 Issue 5 Section 6.2.2(o)
- EN 300 328
- EN 301 489-3
- UL 60950-1
- EN 60950 (European Union)
- CSA C22.2, No. 60950
- EN 55024

LEDS

- Link integrity
- Diagnostic
- Serial activity
- Network activity

PINOUTS

Pin Signal	Description
1 +3.3V	Power (Input)
2 GND	Ground
3 RXD/GPIO7	#1 RXD (Input)/GPIO
4 TXD/GPIO6	#1 TXD (Output)/GPIO
5 RTS/SPI_CLK/GPIO4	#1 RTS (Output)/GPIO/SPI
6 DTR/GPIO5	#1 DTR (Output)/GPIO
7 CTS/GPIO2	#1 CTS (Input)/GPIO
8 DCD/SPI_EN/GPIO1	#1 DCD (Input)/GPIO/SPI
9 DSR/GPIO3	#1 DSR (Input)/GPIO
10 RESET	Reset (Input)
11 RXD2/GPIO9	#2 RXD (Input)/GPIO
12 TXD2/GPIO8	#2 TXD (Output)/GPIO

POWER REQUIREMENTS

- **Digi Connect EM**
 - 3.3Vdc @ 250mA typical (825mW)
- **Digi Connect Wi-EM**
 - 3.3Vdc @ 400mA max (1.32W)

DIMENSIONS

- **Digi Connect EM**
 - Length: 1.935 in (49.149 mm)
 - Width: 1.575 in (40.005 mm)
 - Height: 0.615 in (15.621 mm) (Fully Populated Model)
 - Height: 0.262 in (6.655 mm) (Pin Header Model)
- **Digi Connect Wi-EM**
 - Length: 1.935 in (49.149 mm)
 - Width: 1.855 in (47.117 mm)
 - Height: 0.575 in (14.605 mm) (Fully Populated Model)
 - Height: 0.301 in (7.645 mm) (Pin Header Model)

DIGI SERVICE AND SUPPORT

You can purchase with confidence knowing that Digi is here to support you with expert technical support and a strong five-year warranty. <http://support.digi.com>

Digi International

11001 Bren Road E.
Minnetonka, MN 55343 USA
PH: 877-912-3444
952-912-3444
FX: 952-912-4952
Email: info@digi.com
www.digi.com

Digi International GmbH

Joseph-von-Fraunhofer Str. 23
D-44227 Dortmund
Germany
PH: +49-231-9747-0
FX: +49-231-9747-111
www.digi.de

Digi International (HK) Limited

Suite 1703-05, 17/F.,
K Wah Centre
191 Java Road
North Point, Hong Kong
PH: +852-2833-1008
FX: +852-2572-9989
www.digi.cn

NetSilicon

411 Waverley Oaks Road #304
Waltham, MA 02452 USA
PH: 800-243-2333,
781-647-1234
FX: 781-893-1338
Email: info@netsilicon.com

