

# HelloDevice Lite

## LS100

1.2.0

2004-05-21

HelloDevice LS100

1.2.0

1.2.X

Printed in Korea

Copyright 2002~2004,

. All rights reserved.

가

HelloDevice(tm) , Inc.

Windows(r) Microsoft Corporation

Ethernet(r) XEROX Corporation

가

210

137-130,

Tel: (+82-2) 573-5422

Fax: (+82-2) 573-7710

E-Mail: support@sena.com

Website: <http://www.sena.com>

1:	.....	5
1.1	.....	5
1.2	.....	6
1.3	.....	7
1.4	.....	8
2:	.....	10
2.1	.....	10
2.2	.....	12
2.2.1	.....	12
2.2.2	.....	12
2.2.3	.....	13
2.3	.....	14
2.3.1	.....	14
2.3.2	.....	16
2.4	.....	17
2.4.1	'set'	18
2.4.2	'get'	19
2.4.3	'help'	20
2.4.4	'factorydefault'	21
2.4.5	'save'	22
2.4.6	'exit'	22
2.4.7	'reboot'	22
3: IP	.....	23
3.1 Static IP	.....	24
3.1.1	.....	24
3.1.2 Static IP	.....	24
3.2 DHCP	.....	25
3.2.1	.....	25
3.2.2 DHCP	.....	25
3.3 PPPoE	.....	26
3.3.1	.....	26
3.3.2 PPPoE	.....	26
4.	.....	27
4.1 TCP	.....	30
4.1.1	.....	30

4.1.2	TCP	.....	32	
4.2	TCP	.....	33	
4.2.1		.....	33	
4.2.2	TCP	.....	35	
4.3	TCP	/	.....	36
4.3.1		.....	36	
4.3.2	TCP	/	.....	38
5:		.....	39	
6:		.....	41	
A:		.....	42	
A.1	Pin Outs	.....	42	
A.2	Pin Outs	.....	42	
A.3		.....	43	
A.4		.....	43	
B:		.....	44	
C:		.....	45	
C.1	/LED	.....	45	
C.2		.....	45	
C.3		.....	46	
C.4	IP	.....	46	
C.5	DHCP	.....	46	
C.6	TCP	.....	47	
C.7		.....	47	

1:

1.1

HelloDevice Lite

가

LS100 가

LS100 RS232

LS100 TCP/IP

LAN( )

LS100 telnet

HelloDevice Manager

LS100 /POS, ,

## 1.2

- HelloDevice LS100
- 110V      230V
- /
- 가
- HD -IDE, HD -VirtualCOM, HD -Manager                  가              CD -ROM

### 1.3

	/	DB9	x 1
	1200bps ~ 115200bps		
	: None	RTS/CTS	
	: Rx, Tx, RTS, CTS, DTR, DSR, GND		
	10 Base-T	(RJ45 )	
	IP		
	ARP, IP/ICMP, TCP, Telnet, DHCP client, PPPoE		
	ID		
	Telnet	HelloDevice Manager	
LED	Power		
	Ready		
	10 Base-T Link,		
		Rx/Tx	
Power	:		
	7.5V ~ 15V DC		
	:		
	140mA ( )		
	:		
	0 ~ 55 °C		
	:		
	-4 ~ 66 °C		
	100 mm L (3.9 in.)		
	72 mm W (2.8 in.)		
	29 mm H (1 in.)		
	230g		
	FCC(A), CE(A), MIC		
	5		

## 1.4

LS100

MAC

LAN

MAC(Media Access Control)

가

.( LAN .)

6

OUI(Organization Unique Identifier) 6

12

. LS100 MAC 00-01-95-xx-xx-xx ,

가

IP

"가

(" ").

/  
/

,

/

HTML

HTML

<b>ISP</b>	(Internet Service Provider)
<b>PC</b>	(Personal Computer)
<b>NIC</b>	(Network Interface Card)
<b>MAC</b>	(Media Access Control)
<b>LAN</b>	(Local Area Network)
<b>UTP</b>	(Unshielded Twisted Pair)
<b>ADSL</b>	가 (Asymmetric Digital Subscriber Line)
<b>ARP</b>	(Address Resolution Protocol)
<b>IP</b>	(Internet Protocol)
<b>ICMP</b>	(Internet Control Message Protocol)
<b>UDP</b>	(User Datagram Protocol)
<b>TCP</b>	(Transmission Control Protocol)
<b>DHCP</b>	(Dynamic Host Configuration Protocol)
<b>SMTP</b>	(Simple Mail Transfer Protocol)
<b>FTP</b>	(File Transfer Protocol)
<b>PPP</b>	(Point-To-Point Protocol)
<b>PPPoE</b>	(Point-To-Point Protocol over Ethernet)
<b>HTTP</b>	(HyperText Transfer Protocol)
<b>DNS</b>	(Domain Name Service)
<b>SNMP</b>	(Simple Network Management Protocol)
<b>UART</b>	(Universal Asynchronous Receiver/Transmitter)
<b>Bps</b>	(Universal Asynchronous Receiver/Transmitter)
<b>DCE</b>	(Data Communications Equipment)
<b>DTE</b>	(Data Terminal Equipment)
<b>CTS</b>	가 (Clear to Send)
<b>DSR</b>	(Data Set Ready)
<b>DTR</b>	(Data Terminal Ready)
<b>RTS</b>	(Request To Send)

## 2:


- LS100
- 2.1 LED
  - 2.2 LS100
  - 2.3 telnet
  - 2.4 LS100
- DC ( ) x 1  
( ) x 1  
RS-232 RS-232 x 1  
( NIC) 가 PC x 1 RS232 x 1  
PC x 1

### 2.1

LS100 5 LED 10 Base-T  
2-1 LED 2 가

2 - 1. LED

10 Base-T	Link	10 Base-T
	Act	LS100
	Rx/Tx	LS100 가
	Ready	
	Power	



2-1. LS100


## 2.2

LS100

- LS100
- LS100
- LS100

### 2.2.1

DC   LS100  
, LS100 [Power]




2 - 2. LS100

### 2.2.2

LS100 10Base-T  
, LS100

- LS100 [Link]
- [Act]

LS100




2-3. LS100

### 2.2.3


LS100

LS100




2 - 4. LS100

## 2.3




### 2.3.1

1) LS100



2-5. LS100

2)  
3) /



2 - 6. LS100 /

4) (HyperTerminal)

**9600 Baud rate, Data bits 8, Parity None, Stop bits 1, No flow control**

- 5) [ENTER]
- 6) LS100  
admin
- 7) 가 LS100 2-7

```

login: admin
password: *****
Type 'help' to get command usages
> help
set group par1 [par2 ...] + <CR>
- group = 'ip','host','serial' or 'admin'
- par1 ... = configuration parameters. Use * to keep a parameter's value
get [group] + <CR>
- group = 'ip','host','serial','admin' or 'status'
- If group is specified, shows settings of the group.
- If group is omitted, shows settings of all groups.
factorydefault [option] + <CR>
- if option is omitted, all parameters are set with factory default values.
- if option='-ip',
  all parameters except IP settings are set with factory default values.
help [group] + <CR>
- If group is omitted, shows this screen.
- If group is specified, shows 'set' command usage of the group.
save + <CR>
- Save changes
exit + <CR>
- Exit without rebooting the device
reboot + <CR>
- Exit and reboot the device

>

```

2 - 7. LS100

'set', 'get'      'save'  
 ,                  'exit'      'reboot'  
 'help'

2.4

### 2.3.2

LS100    telnet  
 LS100     가


LS100    IP    telnet    TCP

23

LS100

1) TeraTerm-Pro    telnet    Target IP  
 LS100    23

telnet 192.168.1.254



2 - 8 Telnet

2) LS100

**admin**

3) LS100

4)

## 2.4

LS100

가

2-2 LS100

2 - 2 LS100

set group par1 [par2 ...] + <CR>	<ul style="list-style-type: none"> <li>- group = 'ip', 'host', 'serial'      'admin'</li> <li>- par1 ... =     *</li> </ul>	,	"OK" + <CR> + <LF> If error "ERROR" + <CR> + <LF>
get [group] + <CR>	<ul style="list-style-type: none"> <li>- group = 'ip', 'host', 'serial', 'admin'      'status'</li> <li>- ,</li> <li>- ,</li> </ul>	,	
help [group] + <CR>	<ul style="list-style-type: none"> <li>- ,</li> <li>- ,</li> <li>- ,     'set'</li> </ul>	,	
factorydefault [option] + <CR>	<ul style="list-style-type: none"> <li>- ,     가</li> <li>- if option='ip'      IP     가</li> </ul>	,	"OK" + <CR> + <LF> 가 "ERROR" + <CR> + <LF>
save + <CR>		,	"OK" + <CR> + <LF> 가 "ERROR" + <CR> + <LF>
exit + <CR>	( )	,	"OK" + <CR> + <LF> 가 "ERROR" + <CR> + <LF>
reboot + <CR>			None

## 2.4.1 'set'

'set' LS100 'set'

**set group par1 [par2 ...] + <CR>**

where,

**group = 'ip','host','serial' or 'admin'**

**par1 par2 ... = configuration parameters. Use \* to keep a parameter's value**

'group' , IP 2-  
9 set

```
> set ip static 192.168.1.100 255.255.255.0 192.168.1.1  
OK  
>
```

2 - 9 IP

'static' LS100 'ip' 'ip'  
                  , IP      '192.168.1.100' static IP  
                  IP      IP

```
> set ip static * 255.255.0.0  
OK  
>
```

2 - 10

'set' , IP 'help group'  
                  , IP      'help ip' + <CR>  
                  'help ip'  
2-11         IP      'help ip'

```
> help ip  
set ip ipmode par1 par2 ...  
- ipmode: static=Static IP / dhcp=DHCP / pppoe=PPPoE  
- parameters:  
if ipmode = static,  
    par1 = IP address,  
    par2 = subnet mask,  
    par3 = gateway  
if ipmode = dhcp,  
    no parameters required  
if ipmode = pppoe,  
    par1 = PPPoE username,  
    par2 = PPPoE password  
>
```

2 - 11

	'save'	'reboot'	2.4.5 ~ 2.4.7
--	--------	----------	---------------

## 2.4.2 'get'

'get' LS100 'get'

**get [group] + <CR>**

where,

**group = 'ip', 'host', 'serial', 'admin' or 'status'**

- If group is specified, shows settings of the group.
- If group is omitted, shows settings of all groups.

'set' 가 , IP  
2-12 get

```
> get ip
IP_mode: static
IP_address: 192.168.1.100
Subnet_mask: 255.255.255.0
Gateway: 192.168.1.1
>
```

2 - 12 IP

'status' 'set' 가 'get status'

```
> get status
Serial_no.: LS100-0207_test
MAC_address: 00-01-95-77-88-99
F/W_REV.: V1.2.0
Current_IP: 192.168.0.125
>
```

2 - 13

, get 2-14

```
> get
--- Status ---
Serial_no.: LS100-0207_test
MAC_address: 00-01-95-77-88-99
F/W_REV.: V1.2.0
Current_IP: 192.168.0.125
--- Admin ---
Username: admin
Password: admin
Devicename: LS100 Device
--- IP ---
IP_mode: dhcp
```

```

--- Host ---
Host_mode: tcps
Local_port: 6001
Inactivity_timeout(sec): 300
--- Serial ---
Baudrate: 9600
Data_bits: 8_bits
Parity: None
Stop_bits: 1_bit
Flow_control: None
DTR_option: Always_high
DSR_option: None
Interchar_timeout(ms): 50
>

```

2 - 14

### 2.4.3 'help'

'help'

**help [group] + <CR>**

**where,**

**if group is omitted, overall help screen will be displayed**

**if group is specified, 'set' command usage of specified group will be displayed.**

2-15

2-16 'ip'

```

> help
set group par1 [par2 ...] + <CR>
- group = 'ip','host','serial' or 'admin'
- par1 ... = configuration parameters. Use * to keep a parameter's value
get [group] + <CR>
- group = 'ip','host','serial','admin' or 'status'
- If group is specified, shows settings of the group.
- If group is omitted, shows settings of all groups.
help [group] + <CR>
- If group is omitted, shows this screen.
- If group is specified, shows 'set' command usage of the group.
factorydefault [option] + <CR>
- if option is omitted, all parameters are set with factory default values.
- if option='-ip',
    all parameters except IP settings are set with factory default values.
save + <CR>
- Save changes
exit + <CR>
- Exit without rebooting the device
reboot + <CR>
- Exit and reboot the device

```

2 - 15

```

> help ip
set ip ipmode par1 par2 ...
- ipmode: static=Static IP / dhcp=DHCP / pppoe=PPPoE
- parameters:
if ipmode = static,
    par1 = IP address,
    par2 = subnet mask,
    par3 = gateway
if ipmode = dhcp,
    no parameters required
if ipmode = pppoe,
    par1 = PPPoE username,
    par2 = PPPoE password

```

2 - 16 'ip'

#### 2.4.4 'factorydefault'

'factorydefault'  
'factorydefault'

**factorydefault [option] + <CR>**

**where,**

- if option is omitted, all parameters are set with factory default values.
- if option=-ip, all parameters except IP settings are set with factory default values.

'save'	'factorydefault'
'save'      'reboot'	

```

> factorydefault (or factorydefault -ip)
OK
> save
OK
> reboot

```

2 - 17

#### 2.4.5 'save'

'save' . 'save'

**save + <CR>**

'reboot' LS100

#### 2.4.6 'exit'

'exit'  
LS100 . 'exit'


**exit + <CR>**

#### 2.4.7 'reboot'

'reboot' LS100 . LS100 . 가  
. 'reboot'

**reboot + <CR>**

### 3: IP



<b>Static IP</b>	IP address
	Subnet mask
	Default gateway
<b>DHCP</b>	No parameters required
<b>PPPoE</b>	PPPoE username
	PPPoE password

IP                          'set'

**set ip ipmode par1 par2 ...**

where,

**ipmode:** 'static' for Static IP / 'dhcp' for DHCP / 'pppoe' for PPPoE

**parameters:**

**if ipmode = static,**

**par1 = IP address, par2 = subnet mask, par3 = gateway**

**if ipmode = dhcp,**


**no parameters required**

**if ipmode = pppoe,**

**par1 = PPPoE username, par2 = PPPoE password**

## 3.1 Static IP

### 3.1.1



### 3.1.2 Static IP

LS100 IP set

**set ip static ip\_address subnet\_mask default\_gateway + <CR>**  
where,

**ip\_address = IP address of the LS100**  
**subnet\_mask = Subnet mask**  
**default\_gateway = Default gateway IP address**

3-1 IP 'save' 'reboot'

```
> set ip static 192.168.1.10 255.255.255.0 192.168.1.1  
OK
```

3 - 1. Static IP IP

## 3.2 DHCP

### 3.2.1

(DHCP) 가 IP . DHCP 가 IP  
, ,  
3.1 IP Static IP IP , , ,  
IP 가 DHCP IP , , , DNS  
가 DHCP IP 가  
" (lease)" IP DHCP  
, DHCP IP 가  
LS100 IP DHCP  
DHCP 가 IP , , DNS  
. LS100  
, LS100 DHCP IP DHCP  
LS100 IP DHCP  
IP  
DHCP 가 IP IP  
DHCP , LS100 IP IP  
가 LS100 IP DHCP  
IP LS100 DHCP  
MAC MAC 가  
MAC=00:01:95:04:0c:a1

### 3.2.2 DHCP


LS100 DHCP 3-2 IP DHCP

```
> set ip dhcp  
OK  
>
```

3 - 2. DHCP

### 3.3 PPPoE

#### 3.3.1



#### 3.3.2 PPPoE

LS100 PPPoE 3-3 ADSL PPPoE

```
> set ip pppoe pppoeuser pppoepassword  
OK  
>
```

3 - 3. PPPoE

#### 4.

LS100  
 가 . TCP , , /  
 4-1  
**TCP**

4 - 1. LS100 TCP/IP

TCP	LS100 TCP TCP 가 LS100 TCP 가 TCP 가	LS100 TCP TCP 가 LS100 TCP 가 TCP 가	LS100 TCP 가 TCP 가
TCP	LS100 TCP TCP 가 LS100 TCP 가 TCP 가	LS100 TCP TCP 가 LS100 TCP 가 TCP 가	LS100 TCP 가 TCP 가
TCP / LS100	LS100 TCP TCP 가 ,		

4-2

4 - 2

<b>TCP Server</b>	Listening TCP port
	Inactivity timeout (sec)
<b>TCP Client</b>	Destination IP
	Destination TCP Port
	Cyclic connection Interval
	Inactivity timeout (sec)
<b>TCP Server/Client</b>	Listening TCP port
	Destination IP
	Destination TCP Port
	Cyclic connection Interval
	Inactivity timeout (sec)

'set'

**set host hostmode par1 par2 ...**

where,

**hostmode: tcps=TCP server / tcpc=TCP client / tcpsc=TCP server & client**

**parameters:**

**if hostmode = TCP server (tcps),**

**par1 = listening TCP port,**

**par2 = inactivity timeout (sec)**

**if hostmode = TCP client (tcpc),**

**par1 = destination IP address,**

**par2 = destination TCP port,**

**par3 = cyclic connection interval (min),**

**par4 = inactivity timeout (sec)**

**if hostmode = TCP server & client (tcpsc),**

**par1 = listening TCP\_port,**

**par2 = destination IP address,**

**par3 = destination TCP port,**

**par4 = cyclic connection interval (min),**

**par5 = inactivity timeout (sec)**

**\* set cyclic connection interval to 0 not to use cyclic connection**

**\* set inactivity timeout to 0 for unlimited timeout**

TCP

(State Transition Diagram)

가

LS100 TCP

- Listen

"

"

TCP

TCP

- Closed

"

"

가

[Listen]

TCP

TCP

/

- Sync-Received

TCP

[Listen]


[Sync-

Received]

LS100

[Established]

TCP




## 4.1 TCP

### 4.1.1




1)

[Listen] --> [Sync-Received] --> [Established] --> [Data] --> [Closed] --> [Listen]




2)



가  
"Inactivity timeout"

4-1 TCP



4 - 1. TCP

#### 4.1.2 TCP


LS100    TCP    'set'

**set host tcps listening\_TCP\_port inactivity\_timeout + <CR>**

where,

*listening\_TCP\_port: Listening TCP port*

*Inactivity\_timeout: Inactivity timeout in seconds.*




#### 4-2 TCP

```
> set host tcps 6001 300  
OK  
>
```


Figure 4 - 2. TCP

## 4.2 TCP


### 4.2.1




1)



2)





4 - 3. TCP

#### 4.2.2 TCP

LS100    TCP                          set

**set host tcpc dest\_ip dest\_port cyclic\_connection\_interval inactivity\_timeout + <CR>**


where,

*dest\_ip = destination IP address*

*dest\_port = destination TCP port*

*cyclic\_connection\_interval = cyclic connection interval in minutes*

*inactivity\_timeout = inactivity timeout in seconds.*



**Inactivity timeout**    TCP


4-4    TCP

```
> set host tcpc 192.168.1.1 6001 10 300
OK
>
```

4 - 4 TCP

## 4.3 TCP /

### 4.3.1



1)


[Listen] --> [Sync-Received] --> [Established] --> [Data] --> [Closed] --> [Listen]

Or

[Listen] --> [Sync-Sent] --> [Established] --> [Data] --> [Closed] --> [Listen]



2)



4 - 5. TCP /

#### 4.3.2 TCP /

LS100      TCP      /    'set'

**set host tcpsc listening\_port dest\_ip dest\_port cyclic\_connection\_interval inactivity\_timeout**  
where,

**listening\_port = listening TCP port**  
**dest\_ip = destination IP address**  
**dest\_port = destination TCP port**  
**cyclic\_connection\_interval = cyclic connection interval in minutes**  
**inactivity\_timeout = inactivity timeout in seconds.**

TCP      /    TCP    TCP

4-6    TCP      /

```
> set host tcpsc 6001 192.168.1.100 7001 10 300  
OK  
>
```

4 - 6 TCP      /

## 5:

LS100

5-1

5 - 1.

	Values
Baud rate	1200, 2400, 4800, 9600, 19200, 38400, 57600, or 115200
Data bits	7 bits or 8 bits
Parity	None, Even or Odd
Stop bits	1 bit or 2 bits
Flow control	None, Hardware (RTS/CTS)
DTR option	Always HIGH, Always LOW, Show TCP connection
DSR option	None, Accept TCP connection only by HIGH, Open/Close TCP connection
Inter-character timeout	Inter-character timeout value in milliseconds

'set'

**set serial baudrate data\_bits parity stop\_bits flow\_control dtr\_option dsr\_option interchar\_timeout(ms)**

where,

**baudrate: 1200, 2400, 4800, 9600, 19200, 38400, 57600, or 115200**

**data\_bits: 7=7-bits / 8=8-bits**

**parity: n=none / e=even / o=odd**

**stop\_bits: 1=1-bit / 2=2-bits**

**flow\_control: n=none / h=hardware**

**dtr\_option: h=always high / l=always low / s=show tcp connection**

**dsr\_option: n=none / a=accept only by high / o=open,close TCP connection**

**interchar\_timeout: inter-character timeout value in milliseconds**

```

, , , , 9600 bps, 8 , , 1
. . LS100 . . LS100 7
, , 1 LS100 2 . LS100 8
, ( ) , 2 LS100 1

```

None LS100 RTS/CTS

DTR/DSR    TCP  
     . DTR    , DSR LS100  
**DTR option**    *always high, always low*    *show TCP connection*     가  
     . DTR    DTR                                 TCP  
     HIGH   .  
**DSR option**    *none, allow TCP connection only by high*    *open/close TCP connection*     가  
     .    *Allow TCP connection only by HIGH*                                     가 TCP  
     TCP   DSR                                     가  
     HIGH   . Open/close TCP connection   가 TCP  
    DSR                                     *Open/close TCP connection*                                   ,  
   DSR     HIGH                                     , LOW

**Inter-character timeout**   LS100  
   가    LS100  
  LS100   ,    *Inter-character timeout*  
    TCP/IP  
   Inter-character timeout    baud rate  
    ,    가 1200 bps, 8 Data bits, 1 stop bit   no  
  parity   .   10  
    10 (       ) / 1200 (     /    ) \* 1000 (        /    )=8.3  
  Inter-character timeout   8.3 ms    . Inter-character timeout  
    10 ms

  ,  
    Inter-character timeout    ,  
  LS100    . LS100    1400

**5-1**   9600 bps, 7                                     ,   , 2                                  ,    , DTR   TCP  
   , DSR   , 10 ms    inter-character time-out

```

> set serial 9600 7 e 2 h s n 10
OK
>
  
```

6:

set

**set admin username password devicename**  
*username: login username*  
*password: login password*  
*devicename: device name*

7-1

```
> set admin adminuser adminpassword LS100_test1
OK
>
```


7 - 1

A:

## A.1 Pin Outs

LS100 AT&T258

A-1



A - 1. RJ45


A - 1. RJ45

1	Tx+	
2	Tx-	
3	Rx+	
4	NC	
5	NC	
6	Rx-	
7	NC	
8	NC	

## A.2 Pin Outs

LS100 DB9

A-2




A - 2. DB - 9


A - 2. DB - 9

	RS232
1	-
2	Rx
3	Tx
4	DTR
5	GND
6	DSR
7	RTS
8	CTS
9	-

### A.3




A - 3.



A - 4.

### A.4



A - 5. RS232

## B:

0 1023 , , / 1024 49151  
 49152 65535 .  
 IANA 가 , . 가  
 가 . B - 1  
 IANA

URL <http://www.iana.org/assignments/port-numbers>

B - 1.

		TCP/UDP
21	FTP (File Transfer Protocol)	TCP
22	SSH (Secure SHell)	TCP
23	Telnet	TCP
25	SMTP (Simple Mail Transfer Protocol)	TCP
37	Time	TCP, UDP
39	RLP (Resource Location Protocol)	UDP
49	TACACS, TACACS+	UDP
53	DNS	UDP
67	BOOTP server	UDP
68	BOOTP client	UDP
69	TFTP	UDP
70	Gopher	TCP
79	Finger	TCP
80	HTTP	TCP
110	POP3	TCP
119	NNTP (Network News Transfer Protocol)	TCP
161/162	SNMP	UDP

C:

C.1 /LED

Power LED가		
Link LED가		가 LS100
ACT LED가	IP	IP

C.2

		( )
		. 9600 bps, 8 Data bits, No parity, 1 stop bit, Hardware flow control
	/ 가	/ 가
	IP IP가	DHCP IP 가 DHCP IP가 IP static IP 20
	가	admin

### C.3

Telnet LS100	LS100 가	IP
		telnet
	가	
		admin

### C.4 IP

LS100 IP		IP
		HelloDeviceManager LS100
HelloDeviceManager LS100	LS100 가	IP
	HelloDeviceManager LS100	LS100 PC HelloDeviceManager

### C.5 DHCP

IP	DHCP 가	DHCP 가
LS100 IP 가	DHCP 가	DHCP 가

## C.6 TCP

LS100	IP	IP
	LS100 가 TCP 가	LS100 /
	LS100 IP TCP 가	LS100 IP TCP
	DSR DSR HIGH	DSR LS100 DSR HIGH
	TCP	TCP

## C.7

TCP/IP	가 Inter-character timeout 가	Inter-character tim eout
LS100		LS100
가		